# THE BEST PROTECTION YOU DON'T SEE



With over 25 years in the market Tower-Guard, a Lava-Liner product, has been developed, tested, and implemented in every situation imaginable. With world-class specification, such as being the only Class- A fire rated with ASTM E108 and/or E84 and NFPA 25/50 ratings you can feel confident when applying Tower-Guard to hold up to the test of time and the elements.

## WHY TOWER-GUARD

Tower-Guard has been applied at locations like power plants, data centers, distribution centers, and everything in between. With Tower-Guards specially formulated makeup, it ensures industry leading protection and ease of application regardless of setting.



#### Fire Retardant

Tower-Guard exceeds the standards of ASTM E 108, Standard Method of Fire Tests of Roof Coverings and comparable UL-90 and UBC 15-2 standards and aid in the prevention of Ignition within cooling towers that can be caused by welding or cutting operations, smoking, overheated bearings, electrical failures, and other heat- or spark-producing sources. (NFPA) 214, Standard on Water-Cooling Towers



## **Extreme Properties**

Tower-Guard epoxies and urethanes maintain an impermeable surface with high adhesion and can retain flexibility at temperatures below -60°F (-51°C) and Urethane/Epoxies with flexibility to -22°F (-30°C).



#### **Eco Friendly**

Tower-Guard is designed to contain chemical solutions, reduce water loss and retard and negate development of micro-organisms and prevent leaching into the environment, improve your Water Treatment Program and management.



### Anti Microbial Technology

Antimicrobial properties of several proprietary chemicals components of CEASEFIRE and Tower-Guard impart lifetime protection against the formation of most fungi, biofilm and many bacteria such as Legionella and Pseudomonas.

We work to continously provide the superior solutions with superior customer support.

**Get Information:** 



+ 1 (415) 829-9114



info@tower-guard.com

TOWER-GUARD